



Variable Dimensions	Motor Rating (kW)									
	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	
L1	475	475	475	475	485	485	515	515	530	
L2	645	645	645	645	645	645	645	645	645	
L3*	852	852	872	872	889	914	949	949	969	
L4*	207	207	227	227	244	269	304	304	324	
L5	135	135	135	135	135	135	135	135	135	
L6	110	110	110	110	110	110	110	110	110	
D *	140	140	157	157	164	164	198	198	224	
H *	126	126	135	135	150	150	160	160	179	
Approx Mass (Kg)	Basic	94	94	99	99	101	106	110	110	118
	Per 100 Stroke	10	10	10	10	10	10	10	10	10

For strokes less than 250, dimensions L1, L2 & L3 to be based on 250 Stroke  
 Maximum stroke length: 1600 (For longer strokes consult Dabeb Elram)  
 For strokes of 1000mm and above, increase L1 by 40mm and L2 and L3 by 80mm.

\* These dimensions are nominal, and will vary slightly according to electric motor manufacture.  
 For actuators fitted with piston rod protection bellows, please refer to Data Sheet No OF 24  
 Please consult the optional features section of the catalogue (blue pages) for details of the many options available.

For full specifications and ordering information, see the white pages.  
 Certified drawings are available on request.

In the interests of continued development, we reserve the right to make changes without notice.