



Variable Dimensions	Motor Rating (kW)									
	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	
L1	525	525	525	525	580	580	580	595	615	
L2	775	775	775	775	775	775	775	775	775	
L3*	1002	1002	1019	1044	1079	1079	1099	1140	1178	
L4*	227	227	244	269	304	304	324	365	403	
L5	170	170	170	170	170	170	170	170	170	
L6	140	140	140	140	140	140	140	140	140	
D *	157	157	164	164	198	198	224	248	248	
H *	135	135	150	150	160	160	179	205	205	
Approx Mass (Kg)	Basic	133	133	136	139	145	148	158	172	190
	Per 100 Stroke	12	12	12	12	12	12	12	12	12

For strokes less than 250, dimensions L1, L2 & L3 to be based on 250 Stroke  
 Maximum stroke length: 2500 (For longer strokes consult Dabeb Elram)  
 For strokes of 1000mm and above, increase L1 by 40mm and L2 and L3 by 80mm.

\* These dimensions are nominal, and will vary slightly according to electric motor manufacture.  
 For actuators fitted with piston rod protection bellows, please refer to Data Sheet No OF 24  
 Please consult the optional features section of the catalogue (blue pages) for details of the many options available.

For full specifications and ordering information, see the white pages.  
 Certified drawings are available on request.

In the interests of continued development, we reserve the right to make changes without notice.