



Variable Dimensions	Motor Rating (kW)								
	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	
L1	590	590	590	600	600	600	625	645	
L2	845	845	845	845	845	845	845	845	
L3*	1072	1089	1114	1149	1149	1169	1210	1248	
L4*	227	244	269	304	304	324	365	403	
L5	200	200	200	200	200	200	200	200	
L6	170	170	170	170	170	170	170	170	
D *	157	164	164	198	198	224	248	248	
H *	135	150	150	160	160	179	205	205	
Approx Mass (Kg)	Basic	204	206	210	217	217	229	247	269
	Per 100 Stroke	17	17	17	17	17	17	17	17

For strokes less than 250, dimensions L1, L2 & L3 to be based on 250 Stroke  
 Maximum stroke length: 4000 (For longer strokes consult Dabeb Elram)  
 For strokes of 1000mm and above, increase L1 by 40mm and L2 and L3 by 80mm.

\* These dimensions are nominal, and will vary slightly according to electric motor manufacture.  
 For actuators fitted with piston rod protection bellows, please refer to Data Sheet No OF 24  
 Please consult the optional features section of the catalogue (blue pages) for details of the many options available.

For full specifications and ordering information, see the white pages.  
 Certified drawings are available on request.

In the interests of continued development, we reserve the right to make changes without notice.